

SPECIFICATION SHEET



LAMPROS



Electrical Sdn Bhd


Solar LED Ceiling Light

Type	: Solar Ceiling
Model	: SXD-100, SXD-200, SXD-300, SXD-400
Power	: 100W, 200W, 300W, 400W
Solar Panel	: 6v 6w(100w), 6v 8w(200w) : 6v 12w(300w), 6v 18w(400w)
Li-ion Battery	: 3.2v 4500mA (100w), 3.2v 5500mA (200w) : 3.2v 10000mA (100w), 3.2v 15000mA (200w)
Lumen	600lm (100w), 800lm (200w) : 1200lm (300w), 1800lm (400w)
Color Temperature	6500K
Beam Angle	: 180°
Charging Time	: >6 Hours (In The Sunlight)
Operating Time	: >11-12 Hours (Fully Charged)
Index Protection	: Solar Panel (IP65), Light Casing (IP20)
Wire Length	: 4 Meter
Casing Material	: Polymer
Color	: White
Carton	: SXD100 (10pcs), SXD200 (10pcs) : SXD300 (5pcs), SXD400 (5pcs)




Measurement (mm)


Model	A	B	C	D
SXD100	Ø180	50	190	240
SXD200	Ø230	50	180	270
SXD300	Ø270	50	230	350
SXD400	Ø300	50	350	350



Front View



Side View



Solar Front View



Wireless Remote Controller



Life Span
50,000 Hours



Beam Angle
180°

